



JOHN DEERE 647A QUIK-TRAK COMMERCIAL FRONT MOWER

[For specifications \(click here\)](#)

[Pricing \(click here\)](#)

To compare with other manufacturers models hold down the [Control](#) key on your keyboard and click on the following link:

<http://www.deere.com/specsapp/CustomerCompetitorDetailsServlet?sbu=CCE&userAction=GETCOMPMODELS&pciModel=647A%20TC&displayModelName=647A%20with%2048-inch%20Mower&tM=GC&pNbr=0850TC>

Power

- 19-hp air-cooled, vertical shaft Kawasaki® gas engine
- 8.5 mph transport speed

Hydrostatic System

- Exclusive single-body dual-unitized Kanzaki pump for greater reliability
- Closed loop system eliminates cross contamination possibility
- 2-gallon (U.S.) reservoir allows a longer "dwell time" - enabling system to run cooler

Dual-Lever Loop Drive Control

- Intuitive operation for both new and experienced operators
- Ergonomically designed for rider comfort during extended operations
- Zero turning radius for excellent maneuverability

7-Iron II™ Deep-Deck Mowers

- 48-inch 7-Iron II™ commercial mower deck
- Provides a powerful vacuuming action to lift the grass and create better airflow
- One-piece 7-gauge stamped steel means no weld points to fail
- Full floating deck follows ground contours, providing the best groomed appearance

Deck Height Adjustment

- No-tool height-of-cut adjustment from platform
- Fifteen height-of-cut positions from 1.5 inches to 5 inches in 1/4-inch increments
- Operator can change height of cut without leaving the operator platform

Spindles

- Ribbed cast aluminum spindle housings provide strength and cooling surface area that stands up to commercial applications
- Three 25mm spindles are cold-forged and heat treated for added strength
- Spindles are supported by precision ball bearings, providing enduring performance and reliability
- Spindles can be greased from the top of the mower deck

Large Fuel Capacity

- Single-fill 6 U.S. gallon fuel tank
- Top-draw dual tank for added safety

Comfortable, Two-Inch Thick Leaning Pad

- Two-inch-thick pad absorbs shock, providing a more comfortable ride for all-day mowing
- Pad is also insulated for protection against engine heat

Serviceability

- Top-mounted grease zerks on spindles for daily maintenance
- Open engine compartment allows full access to engine components for easy maintenance and serviceability

Safety

- Bilingual (English and Spanish) safety decals and operational safety video

Two-Year "Bumper-to-Bumper" Limited Warranty*

- Local John Deere Dealer takes care of all warranty service. (There's no need to go to component suppliers for service.) *See dealer for details.

Product features are based on published information at the time of publication. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Product features are subject to change without notice. Product options and accessories may not be available in all regions. Contact tome@cpebry.com for more detailed information.